

Artista[®] CR805 Retransfer Printer with Card Lamination Module

HIGHLIGHTS Designed for possibilities

The Entrust Artista® CR805 Retransfer Printer with Card Lamination Module gives customers a complete, on-demand card-printing solution with stunning color, increased speed, security features, and the durability needed to create virtually any type of card for customers, citizens, and employees.

- Superior image quality
- Expanded modularity
- Issuance security architecture
- Increased speed
- Increased durability
- Cloud compatible (coming soon).

KEY FEATURES & BENEFITS

Get a high-end look for every card design

 600-dpi resolution retransfer printing provides precise, photo-quality imagery as well as microtext, bar codes, and other machine-readable elements

- Pigment ink prints lifelike skin tones so you can more accurately authenticate each cardholder to improve security
- Over-the-edge printing with retransfer technology allows you to print on multiple card types, including technology cards
- On-demand printing means you can print exactly the design you need, eliminating the need for pre-printed cardstock

Unmatched security

- Optional locks
- Secure boot protects system from malware or virus on boot-up
- Trusted Platform Module (TPM) manages the printer's own TLS/SSL certificates and keys
- Connection and data sent between software and printer is encrypted
- Customer data is encrypted and is not stored in the printer after printing is complete
- UV printing and other security features added to cards protect from tampering and counterfeiting

Issue more durable cards and save on replacement costs

- Pigment ink provides longer-lasting images with resistance to UV fading
- Primerless ribbons have a unique pigment ribbon formation that does not require a primer panel, enabling faster print speeds of 110 cards per hour
- Extend card durability with primerless ribbons. The combination of primerless color ribbon and unique retransfer film improves card durability up to 50% greater in adhesion and abrasion resistance
- Primerless ribbons offer cost savings as a value-priced solution over original primer supply options
- Retransfer film adds a layer of durability; apply two for more protection
- Card lamination module provides enhanced durability and security





TECHNICAL SPECIFICATIONS

CR805 Printer Standard Features and Specifications

| Print technology | Retransfer pigment ink |
|-----------------------|---|
| Print capabilities | Single or dual-sided, over-the-edge printing |
| Print resolution | 600 dots per inch (dpi) |
| Print speed | Full-color printing Single-sided (CMYK) – up to 110 cards per hour (cph) Double-sided (CMYK-K) – up to 65 cards per hour (cph) |
| Color modes | True Color (ICC) – prints color as close as possible to image as defined in the card design Legacy SR/CR – prints as close as possible to the SR200, SD300, and SR300e card printers Vivid – printer colors with higher saturation and contrast |
| Card capacity | Input hopper – up to 125 cards Output hopper – up to 25 cards (Optional 125-card hopper) Card input size – 0.030 inches to 0.040 inches (0.76 mm to 1.01 mm) |
| Operating environment | 60°F - 95°F (15°C - 35°C) |
| Physical dimensions | L 21.4 in. x W 10.1 in. x H 15.6 in. / L 54.34 cm x W 25.53 cm x H 39.68 cm |
| Weight | 28 lb. (12.7 kg); will vary with options |
| Connectivity | USB and Ethernet |
| Warranties | Printer: 36-month standard warranty / Printhead: Limited lifetime warranty |

| Magnetic stripe encoding | ISO/IAT Magnetic Stripe Encoding / JIS Magnetic Stripe Encoding |
|--|--|
| Multi-Hopper | Six-compartment multi-hopper (Six 125-card hoppers, 750-card total capacity) |
| WiFi | WiFi types: 802.11g/n Authentication modes: None, WPA2 Personal Dual-band 2.4GHz & 5GHz |
| Smart card encoding | Single wire - Contact ISO 7816 T=0, 1 Contactless ISO 14443 A/B Protocols, MIFARE Protocols & FeliCa (DES & AES) Loosely coupled - Contact ISO 7816 T=0, 1 HID iCLASS, read/write or read-only encoder PC Prox |
| Primerless color panel ribbons and retransfer film | CMYK - 1,000 images simplex - 500 duplex CMYK-K - 1,000 images duplex Clear retransfer film - 1,000 simplex - 500 duplex |
| Color ribbons with primer panel and retransfer film | CMYKP-KPi – 500 images dual-sided FCMYP-KPi – 750 images dual-sided Clear retransfer film – 1,500 images single-sided (750 dual-sided) 1,000 images single-sided (500 dual-sided) |

For more information 888.690.2424 +1 952 933 1223 sales@entrust.com entrust.com

ABOUT ENTRUST CORPORATION

Entrust keeps the world moving safely by enabling trusted identities, payments and data protection. Today more than ever, people demand seamless, secure experiences, whether they're crossing borders, making a purchase, accessing e-government services, or logging into corporate networks. Entrust offers an unmatched breadth of digital security and credential issuance solutions at the very heart of all these interactions. With more than 2,500 colleagues, a network of global partners, and customers in over 150 countries, it's no wonder the world's most entrusted organizations trust us.

Distributed by:

erything identification





Entrust and the hexagon logo are trademarks, registered trademarks, and/or service marks of Entrust Corporation in the U.S. and/or other countries. All other brand or product names are the property of their respective owners. Because we are continuously improving our products and services, Entrust Corporation reserves the right to change specifications without prior notice. Entrust is an equal opportunity employer. ©2021 Entrust Corporation. All rights reserved. DP22Q2-artista-cr805-retransfer-clm-ds



Global Headquarters 1187 Park Place, Minneapolis, MN 55379 U.S. Toll-Free Phone: 888 690 2424 International Phone: +1 952 933 1223