

Sigma DS1 Direct-to-Card Printer

HIGHLIGHTS

Sigma: The next generation of direct-to-card printing

Entrust Sigma ID Card Printers are specifically designed for today's cloud environments and give you the ability to easily issue secure identities.

- Simple: From unboxing to issuing ID cards and mobile flashpasses to managing your printer, we made sure Sigma was the most user-friendly ID card issuance solution in the world
- Secure: Our industry-leading issuance security architecture will help protect your cards and your customers' data during each step of the issuance process
- **Smart:** Forward-thinking technology and scalability allow you to expand your ID card program as your needs evolve

KEY FEATURES & BENEFITS

The world's most user-friendly ID card printer

< 1 >

- Intuitive printer dashboard lets you see printer status, order supplies, check cleaning status, update firmware, or contact help – all from your mobile device
- Seamless self-service lets you access how-to videos and other helpful resources by simply scanning QR code on the LCD display
- Variable LED light ring lets you incorporate brand colors or other customization into your ambient environment
- Pre-loaded ribbon cassettes make switching ribbons easy

Unmatched security

- Secure boot protects system from malware or virus on boot-up
- Trusted Platform Module (TPM) manages the printer's own TLS/SSL certificates and keys
- Connection and data sent between software and printer is encrypted
- Customer data is encrypted and is not stored in the printer after printing is complete
- Luster printing and other security features added to cards protect from tampering and counterfeiting

Flexibility and scalability built for the future

- Issuance capabilities include physical cards and digital mobile flashpass
- Choose on-premises or cloud-hosted deployment
- Print anytime, anywhere with your mobile device (iOS, Android, Windows)



TECHNICAL SPECIFICATIONS

Standard Features & Supplies		
Print technology	Dye sublimation	
Print capabilities	Single-sided	
Print resolution	300 dots per inch (dpi) (300 X 600, 300 X 1200)	
Print speed	Single-sided color ribbon: Up to 175 cards per hour (cph)	
Card capacity	Input hopper – 125 cards Output hopper – 25 cards	
Card sizes	Thickness: 0.010 inches to 0.040 inches (0.25mm - 1.016mm) Dimension: ID-1, CR-79	
Operating environment	Temperature: 60°F to 95°F (15°C to 35°C) Humidity: 20-80% RH – non condensing	
Physical dimensions	L 17.4 in x W 8.9 in x H 9 in / 44.2 cm x 22.6 cm x 22.9 cm	
Weight	11.3 lbs (5.49 kg)	
Connectivity	USB	
Warranty	36 months	



Optional Features & Supplies

Magnetic stripe encoding	ISO 7811 three-track support (high- and low-coercivity) JIS Type II single-track option			
WiFi	WiFi types: 802.11g/n Authentication modes: None, WPA2 Dual-band 2.4GHz & 5GHz			
Color ribbons*	YMCKT	250/500 images		
	ymcKT	650 images		
	YMCKT-KT	350 images		
	KT	1000 images		
	KTT	750 images		
	YMCKF-KT	300 images		
	YMCKL-KT	300 images		
	ST-KT	500 images		
Monochrome ribbons		Black, white, blue, red, green, scratch-off, silver matte, gold matte, silver metallic, and gold metallic: 1500 images		

* Color ribbon guide: Y=Yellow, M=Magenta, C=Cyan, K=Black, T=Topcoat, F=UV fluorescent, L=Luster, y=1/2 panel Yellow, m=1/2 panel Magenta, c=1/2 panel Cyan, S=Silver matte, G=Gold matte.



Entrust is a trademark, registered trademark, and/or service mark of Entrust Corporation in the United States and/or other countries. ©2020 Entrust Corporation. All rights reserved. DS21Q1-Sigma-DS1-Direct-to-Card-Printer-DS