



Swiftpro[®] K30D Double Sided

Retransfer Card Printer

Swiftpro provides market-leading solutions with an extensive range of retransfer desktop solutions to meet the needs of the customer and by adding value to global businesses. Our mission is to revolutionize business identity and access management by building trusted partnerships through our simple SMART[™] partner distribution networks.

The Swiftpro K30D retransfer card printer has an outstanding print quality for single and double sided printing. With 300dpi printing density, it is the ideal solution for businesses requiring high-quality identification cards, passes, and badges with personalized physical and logical access management.

The ultra-fast, powerful Swiftpro K30D printer is available with contact and contactless smart code encoding technologies and 100-card input and output hoppers, with an optional 250-card input hopper upgrade. This reliable and durable printer is the ideal solution for both entry level to advanced secure card programs for a range of vertical markets.

Selecting the right printer is important. Equally if not more important is using Genuine Swiftpro Supplies. They are critical to delivering printer reliability, print quality and vibrant colors for your card programs. Swiftpro supplies deliver consistency and ensure the longevity of your printer and print head and minimize downtime and create efficiencies in your card programs. Always ask for Genuine Swiftpro Supplies from your Authorized Premiere Value Added Distributor, Premiere Enterprise Solution Provider or Premiere Value-Added Reseller.

>))) 3032 0514 2106 4502 3038 03/14 (35%) JACOB FAULKNER

111

Swiftpro[®]



The ribbon erase function prevents leakage of personal information on the monochrome black panel ink ribbon. It scrambles information beyond recognition to protect this data.

-

ERSATILIT

Swiftpro's modular design permits customers to upgrade as their card programs need changes.

MAGE QUALITY

High Resolution printing using 300dpi printing provides superior print quality for all your card programs.



by and is the property of same from Matter

RELIABILITY

Swiftpro K-Series are well respected globally for their Japanese engineering for quality and reliability.

NNOVATION

Innovating since the 90's with state of the art retransfer printers, providing safe, secure, and reliable ID card printer solutions to global organizations since 1989.

DURABILITY

Highly durable printers with industry leading warranties on all our products and lifetime on the print head.



Swiftpro K30D Double Sided

Retransfer Card Printer

















Bas 7 9 29

Printing

Dye Sublimation RetransferFull Color Retransfer printingSingle and Double Sided PrintingUp to 64 Cards Per Hour256 Gradation PrintingOver the Edge Printing on CR80, ID-1 Cards

Standard Features

USB & Ethernet connectivity
100-Card Input Hopper (30mil)
100-Card Output Hopper (30mil)
LCD Panel
300 DPI Print Resolution
36 Month Printer Warranty
Lifetime Printhead Warranty
Microsoft Certified Drivers
Solenoid Electronic Lock for Card Input Hopper
Solenoid Electronic Lock for Supplies / Front Door Housing
Software-controlled Lock/Unlock from Status Monitor
K Ribbon Erase Function
IpSec Security for Secure Data Encryption IPv6 and IPv4
Inline Bend Remedy
MAC Address Forced Printing (UV Panel on Card)
Kensington Lock



Swiftpro[°]

Technical Support: supporttech@swiftpro-printer.com | 732-271-7328 Sales: sales@swiftpro-printer.com | 732-271-7369 www.swiftpro-printer.com

Encoding

Magnetic Stripe ISO High/Low Coercivity Encoder Contactless Encoder, Omnikey 5127 (iClass, Mifare and Desfire) Contact Encoder (CF-7CRW / Control board) Contact Encoder (CF-7CCS / IC Contact Station)

Software Supported

CardPresso Card Exchange All Card Personalizations software used through Swiftpro Driver* *check with Software vendor, as some features may be limited for use on Swiftpro Printers Microsoft® Windows® 7, 8, 10 32bit / 64bit Microsoft® Windows® Server 2008 R2 (SP1) 64bit Microsoft® Windows® XP Server 2012 64bit

Swiftpro Genuine Color Ribbons

YMCK - 1000 Yield YMCKK - 750 Yield YMCKP Peel Off Ribbon - 750 Yield YMCKU UV - 750 - Yield InTM Retransfer Film - 1000 Yield

Physical Specification		
Height	13.19 in (335 mm)	Without Card Stacker
Width	13.5 in (343 mm)	Without Card Stacker
Depth	12.68 in (322 mm)	Without Card Stacker
Weight	29.76 lb (13.5 kg)	

Interface

USB 2.0 (Hi-speed / Full Speed) Ethernet (100BASE-TX / 10BASE-T)

Option

Flipper Unit Bend Remedy

Electrica

Temperature: 59°F to 86°F (15°C to 30°C) Humidity: 35% to 70% (YMCK ink, No Condensation) 3.5A (110V system) 1.6A (220V system) 310W (maximum power when all options are installed)

Card Specification

Card Thickness 10-40mil Card Size ISO 7810 Format, CR80, ID-1 Card Material: PVC, PC, PET, PET-G Technology Cards Contact and or Contactless with and Without Mag Stripe

Safety Standards

Agency Listing: UL, CE, FCC, KC, CCC, CSA

KANEMATSU USA

logo are either registered trademarks or trademarks of Kanematsu Corporation (or one of its subsidiaries) in the United States and/or other countries.